

326.4.01 Limits

General Provisions 101 through 150.

326.5 Payment

Portland cement concrete subbase will be paid for at the Contract Unit Price per square yard (meter) for each specified thickness shown on the plans. This payment will be full compensation for:

- Providing Portland cement and all other materials
- Applying first and second applications of curing compound
- Providing all equipment and labor
- Mixing
- Hauling
- Providing other incidentals necessary to complete the Item
- Replacing subbase when required

Payment will be made under:

Item No. 326	Portland cement concrete subbase ____ in (mm) thick	Per square yard (meter)
--------------	---	-------------------------

326.5.01 Adjustments

General Provisions 101 through 150.

Section 327—Mining, Crushing, and Stockpiling Aggregates

327.1 General Description

Specifications for this work will be included elsewhere in the Contract.

Section 328—Foamed Asphalt Stabilized Base Course

328.1 General Description

Specifications for this work will be included elsewhere in the Contract.

Section 400—Hot Mix Asphaltic Concrete Construction

400.1 General Description

This work includes constructing one or more courses of bituminous plant mixture on the prepared foundation or existing roadway surface. The mixture shall conform with lines, grades, thicknesses, and typical cross sections shown on the Plans or established by the Engineer.

This section includes the requirements for all bituminous plant mixtures regardless of the gradation of the aggregates, type and amount of bituminous material, or pavement use.

Work will be accepted on a lot-to-lot basis according to the requirements of this Section and Section 106.

400.1.01 Definitions

Segregated Mixture: Mixture which lacks homogeneity in HMA constituents of such a magnitude that there is a reasonable expectation of accelerated pavement distress or performance problems. May be quantified by measurable changes in temperature, gradation, asphalt content, air voids, or surface texture.

New Construction: A roadway section more than 0.5 mile (800 m) long that is not longitudinally adjacent to the existing roadway. If more than one lane is added, and any of the lanes are longitudinally adjacent to the existing lane, each lane shall be tested under the criteria for a resurfacing project.